VAPOR BARRIER PLACED ON TOP OF THE WOOD DECKING 26 GA. PBR PANEL COLOR BY OWNER

METAL ROOF PANEL

WITH A UL90 UPLIFT RATING -5/8" MIN. DECKING PLACED ON TOP OF 2 X 8 WOOD RAFTERS FR- 30 BATT INSULATION -2X8 RIM BD. TOP OF DBL. PLATES ELEVATION 108.396' HURRICANE CLIPS ---26 GA. PBR PANEL SOFFIT COLOR BY OWNER TOP OF 6"X8" BEAM HURRICANE CLIPS

© EA. RAFTER 7/16" OSB SHEETS TOP OF 2X4 PLATES ON THE CEILING OF THE STORAGE ROOM 1 X 4 GIRT ELEVATION 109.099' ELEVATION 108.880' 2 X 4 DOUBLE PLATES — AT TOP OF STUDS 26 GA. PBR —METAL PANEL COLOR BY OWNER L26 GA. PBR PANEL SOFFIT COLOR BY OWNER -----8" RAFTER @ 16" O.C. EA. WAY 2 X 4 DOUBLE PLATES 6" X 8" WOOD BEAM WRAPPED WITH MTL. TRIM SAMSON STRONGTIE SAMSON STRONGTIE 1 X 4 GIRT 1 X 4 GIRT R-11 BATT INSULATION 4 X 6 WOOD POST WRAPPED WITH MTL. TRIM R-11 BATT INSULATION -7/16" ZIP BD -—5/8" SHEATHING PLACED BETWEEN 1 X 4 FOR INSUL. SUPPORT 4" STUDS @ 16" O.C. 1 X 4 GIRT -5/8" GYP. BOARD WITH 1 X 4 GIRT FRP PANELS IN BOTH BATHROOMS AND CONCESSION AREA 26 GA. PBR METAL PANEL COLOR BY OWNER \_\_ 5/8" X-RATED GYP. BOARD IN STORAGE ROOM 26 GA. PBR —METAL PANEL COLOR BY OWNER 5/8" GYP. BOARD WITH
FRP PANELS IN BOTH BATHROOMS
AND CONCESSION AREA 1 X 4 GIRT -1 X 4 GIRT DOWNSPOUT-1/2" ANCHOR BOLT PLACED
AT BOTTOM OF STUD WALL AT 3'-0" O.C. 1/2" ANCHOR BOLT PLACED
AT BOTTOM OF STUD WALL
AT 3'-0" O.C.

2X4 SILL PLATE SITTING
ON A 1/4" FOAM
MOISTURE BARRIER ON A 1/4" FOAM MOISTURE BARRIER 1 X 4 GIRT -TOP OF FINISH FLOOR
ELEVATION 100.0' — ELEV. =100'-0" CONCRETE FLOOR 4 X 6 WOOD POST
IS ANCHORED TO THE
CONC. WITH A METAL STRAP
THAT IS BOLTED AT THE BOTTOM MTL. FLASHING -TOP OF CONCRETE
ELEVATION 99.75' MTL. FLASHING METAL PANEL 2" CONC. NOTCH

WALL SECTION (TYP.)

DATE: 06/09/2021

JOB #6

REVISION: 06/23/2021 06/29/2021

COPY RIGHT ALL RIGHTS RESERVED:

PLOT SCALE: 1" = 1'-0"

SHEET NO.:

<u>A101</u>